


# Ground Rod Clamp, Rod to Conductor, Stainless Steel – SP58



- Unique stamped body design will not crack from excessive torque
- Provides a greater surface area contact to allow improved performance of the connector
- Compatible with copper, copper bonded, galvanized, stainless steel, rebar and plain steel ground rods and electrodes



Part Number	SP58
Material	Stainless Steel 304 (EN 1.4301)
Torque (TQ)	150 – 300 in lb
Ground Rod Diameter, Nominal	1/2" – 5/8"
Ground Rod Diameter, Actual (Ø)	0.500" – 0.625"
Conductor Size	#12 Stranded - #2 Stranded 4 mm <sup>2</sup> Stranded - 25 mm <sup>2</sup> Stranded
Wrench Size	1/2"
Certifications	cULus
Standard Packaging Quantity	50 pc
UPC	78285660651
EAN-13	8711893094015

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

#### WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at [erico.pentair.com](http://erico.pentair.com) and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.