

Industrial Grade

BACK AND SIDE WIRED/FRONT WIRED - MOTOR STARTING U S

Description	Color	Cat No.				
Rating		30A - 600VAC				
		Max HP Rating	Switch In Steel Type 1 Encl.	Switch In Steel Type 3R Encl.	Switch In Type 4X Encl.*	Switch Only
Double-pole, single-throw without overload protection Disconnect Rated	Black	2HP 120VAC 5HP 240VAC 10HP 480VAC 15HP 600VAC	N1302-DS	N3302-DS	MS4X-302	MS302-DS
Disconnect marked Enclosure ONLY	Black		N13NC-DS	N33NC-DS	—	—
Double-pole - Short Toggle Version Disconnect Rated	Black	2HP 120VAC 5HP 240VAC 10HP 480VAC 15HP 600VAC	—	—	—	MS302-DSS
Three-pole, single-throw without overload protection Disconnect Rated	Black	3HP 120VAC 7.5HP 240VAC	N1303-DS	N3303-DS	MS4X-303	MS303-DS
	Black	15HP 480VAC	N1303-TDS**	—	—	—
	Thermoplastic	20HP 600VAC				
Disconnect marked Enclosure ONLY	Black		N13NC-TDS**	—	—	—
	Thermoplastic					
Three-pole - Short Toggle Version Disconnect Rated	Black	3HP 120VAC 7.5HP 240VAC 15HP 480VAC 20HP 600VAC	—	—	—	MS303-DSS
Rating		40A - 600VAC				
Double-pole, single-throw without overload protection Disconnect Rated	Black	2HP 120VAC 5HP 240VAC 10HP 480VAC 15HP 600VAC	—	—	MS4X-402	MS402-DS
Three-pole, single-throw without overload protection Disconnect Rated	Black	3HP 120VAC 7.5HP 240VAC 15HP 480VAC 20HP 600VAC	—		MS4X-403	MS403-DS
Rating		60A - 600VAC				
Double-pole, single-throw without overload protection Back Wired	Black	10HP 240VAC 15HP 480VAC 20HP 600VAC	—		—	MS602-BW
Double-pole - Front Wired	Black	10HP 240VAC 15HP 480VAC 20HP 600VAC	—	N3602	—	MS602-FW
Three-pole, single-throw without overload protection Back Wired	Black	10HP 240VAC 25HP 480VAC 30HP 600VAC	—		—	MS603-BW
Three-pole - Front Wired	Black	10HP 240VAC 25HP 480VAC 30HP 600VAC	—	N3603	—	MS603-FW
Enclosure ONLY	Black		—	N36NC	—	—

* 4X Enclosures are high impact Valox™ in watertight enclosure rated rated 4X, 3R, 12K and IP67.

** Enclosure has black thermoplastic cover with steel box.