

# Aluminum Flood-Seal® 95 Series Service Entrance Connectors

Suitable for direct burial or installation in an enclosure.




FS 95-6

Features	Benefits/Descriptions
Single-Hole Drilled	Ideal for residential applications.
Dual-Rated	Use with aluminum or copper lugs from #12 to 350 kcmil.
All Outlets and Lugs (See Kits Below) Approved for Full Cable Rating	Safe and reliable.
All Connectors Are 100% Hi-Pot Tested at 4000V for 60 Seconds	Ensures that connectors are 100% watertight and molded correctly.
RUS Accepted	Approved by the federal government for utility use.

## Ordering Information for 95 Series Service Entrance Connectors

CAT. NO.	Outlets	L
FS 95-2	2	2 $\frac{3}{4}$
FS 95-3	3	4 $\frac{1}{4}$
FS 95-4	4	5 $\frac{3}{4}$
FS 95-5	5	7 $\frac{1}{4}$
FS 95-6	6	8 $\frac{3}{4}$
FS 95-7	7	10 $\frac{1}{4}$
FS 95-8	8	11 $\frac{3}{4}$
FS 95-9	9	13 $\frac{1}{4}$
FS 95-10	10	14 $\frac{3}{4}$



URD Connectors &amp; Covers

# Flood-Seal® 95 Series Terminal Kits

Kits have insulating outlet sleeve or heat-shrink sleeve and lug.

Features	Benefits/Descriptions
Three Die Sets Install the Complete Range of Lugs, from #8 to 350 kcmil	Universal use.
Lugs Prefilled with Oxide-Inhibiting Compound and Capped	Prevent oxidation and keep out moisture.



CFB 350 CS

## Ordering Information for 95 Series Terminal Kits

Force-Fit Kit CAT. NO.	Heat-Shrink Kit CAT. NO.	Concentric	Compressed	Compact	Solid	Die Reference
CFG 8 CS	CFG 8 HS	#8	—	—	#6	%, BG, 687, 243, TU, 52, 8A
CFG 6 CS	CFG 6 HS	#6	#6	#6	—	
CFG 4 CS	CFG 4 HS	#4	#4	#4	—	
CFG 2 CS	CFG 2 HS	#2	#2	#2 & #1	#1	
CFG 1 CS	CFG 1 HS	#1	#1	1/0	1/0	
CFG 1/0 CS	CFG 1/0 HS	1/0	1/0	2/0	2/0	
CFK 1/0 CS	CFK 1/0 HS	1/0	1/0	2/0	2/0	840, 324, 249, 658, TX, 76, 11A
CFK 2/0 CS	CFK 2/0 HS	2/0	2/0	3/0	3/0	
CFK 3/0 CS	CFK 3/0 HS	3/0	3/0	4/0	4/0	
CFK 4/0 CS	CFK 4/0 HS	4/0	4/0	250	—	
CFK 250 CS	CFK 250 HS	250	250	300	—	1 $\frac{1}{2}$ -1, 299-655, 96, 13A, 321, 326
CFB 250 CS	CFB 250 HS	250	250	300	—	
CFB 300 CS	CFB 300 HS	300	300	350	—	
CFB 350 CS	CFB 350 HS	336.4-350	350	350	—	

NOTE: For a hex-headed bolt, add "-H" suffix to the catalog number.

Force-Fit Kit includes (1) dual-rated aluminum center-formed lug, (1)  $\frac{3}{8}$ " Allen head mounting bolt, (1) Belleville washer and (1) insulating Flood-Seal® rocket.

Heat-Shrink Kit includes (1) dual-rated aluminum center-formed lug, (1)  $\frac{3}{8}$ " Allen head mounting bolt, (1) Belleville washer and (1) heat-shrink tubing.