



Product Datasheet


ANDERSON FARGO

SEDA3318SSAC -- Compression Deadend



Compression Deadend, Conventional 2-Die, Single Tongue, for ACSS 795.0 kcmil 45/7, With Terminal

Product Specifications

<p>Category Image</p>	 <p>Compression Deadend Assemblies</p> <p>Aluminum</p> <p>Conventional (two die)</p> <p>AAC, ACSR, & ACSS Conductor</p>
<p>Series Image (Comp Assy)</p>	<p>□</p>
<p>PDF Catalog Page</p>	<p>Click HERE to view the web page.</p>
<p>Terminal Option</p>	<p>With</p>
<p>Style</p>	<p>Conventional 2-Die, Single Tongue</p>
<p>Outside Diameter</p>	<p>1.063 in</p>
<p>Type</p>	<p>Compression</p>
<p>Material</p>	<p>Aluminum/Steel</p>
<p>Compression Method</p>	<p>Conventional (2 die system)</p>
<p>Aluminum Die</p>	<p>30AH</p>
<p>Steel Die</p>	<p>10SH</p>
<p>Minimum Press (Tons)</p>	<p>60</p>
<p>Voltage Application</p>	<p>EHV & Std</p>
<p>Inhibitor Loaded</p>	<p>No</p>
<p>Body Material</p>	<p>Seamless Extruded Aluminum Alloy</p>
<p>Eye Material</p>	<p>Galvanized Forged Steel</p>

Terminal Material	Seamless Extruded Aluminum Alloy
Hardware Material	Aluminum Alloy
Length before Compression	21.8 in (554 mm)
Dimension A	2.62 in (66.5 mm)
Dimension B	1.24 in (31.5 mm)
Dimension C	0.55 in (14.0 mm)
Pad Width	3.0 in (76 mm)
Bolt Holes	4
Conductor Range Minimum - Maximum	ACSS 795.0 kcmil (45/7) Tern
Weight / Ea.	9.4 lbs
Standard Package	1
UPC Code	09635938018

Notes

To specify double-tongue deadend, change first character of Catalog Number from S to D.

Compressed Product Number

SEDA3318SSAC



Dimensions

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.